

Slide 1

### Administrivia

- Reminder: Homework 2 due today (11:59pm).

Slide 2

### Minute Essay From Last Lecture

- A couple of people mentioned the first “problem” (learning more about text editing tool(s)).
- Hard to remember to put semicolons in C but not Scala.
- Seconds-calculator program familiar from other languages. (That’s kind of the goal — revisit problems you know how to solve in another language.)
- “Compiling and executing code feels less natural” — it’s all in what you’re used to, maybe?
- “Is `#include` like `import` in Scala?” Kind of, but not really.

## Repetition — Loops

Slide 3

- C, like most/many procedural languages, offers several syntaxes for repetition. Recursion (last time) is one, but often not the most straightforward.
- All have some way of expressing common elements (explicitly, rather than the “do for all” syntax allowed by some languages):
  - *Initializer* (as its name suggests).
  - *Condition* (determines whether repetition continues).
  - *Body* (code to repeat).
  - *Iterator* (something that moves on to next iteration).

## while Loops

Slide 4

- Probably the simplest kind of loop. You decide where to put initializer and iterator. Test happens at start of each iteration.
- Example — print numbers from 1 to 10:

```
int n = 1;                /* initializer */
while (n <= 10) {        /* condition */
    printf("%d\n", n);   /* body */
    n = n + 1;           /* iterator */
}
```
- Various short ways to write `n = n + 1`:

```
n += 1;
n++;
++n;
```

What do you think happens if we leave out this line?

## for Loops

- Probably the most common type of loop. Particularly useful for anything involving counting, but can be more general. Syntax has explicit places for initializer, condition, iterator (so it's less likely you'll forget one of them).

- Example — print numbers from 1 to 10:

```
for (int n = 1; n <= 10; ++n) {  
    printf("%d\n", n);  
}
```

- Initializer happens once (at start); condition is evaluated at the start of each iteration; iterator is executed at the end of each iteration. (Note that C89 standard required that `n` be declared outside the loop.)

Slide 5

## do while Loops

- Looks very similar to `while` loop, but test happens at end of each iteration.

- Example — print numbers from 1 to 10:

```
int n = 1;                                /* initializer */  
do {  
    printf("%d\n", n);                    /* body */  
    n = n + 1;                            /* iterator */  
} while (n <= 10);                        /* condition */
```

Slide 6

### Loops — Example

- Simple example — loop to read integers and compute their sum. (Don't we need a place to store them all? No!)
- (Variant of example in book.)

Slide 7

### Arrays

- Previously we've talked about how to reserve space for a single number/character and give it a name.
- Arrays extend that by allowing you to reserve space for many numbers/characters and give a common name to all. You can then reference an individual element via its *index* (similar to subscripts in math).

Slide 8

## Arrays in C

- Declaring an array — give its type, name, and how many elements.

Examples:

```
int nums[10];  
double stuff[N];
```

(The second example assumes N is declared and given a value previously. In C89, it had to be a constant. In C99, it can be a variable.)

- Referencing an array element — give the array name and an index (ranging from 0 to array size minus 1). Index can be a constant or a variable. Then use as you would any other variable. Examples:

```
nums[0] = 20;  
printf("%d\n", nums[0]);
```

(Notice that the second example passes an array element to a function. AOK!)

Slide 9

## Arrays in C, Continued

- We said if you declare an array to be of size  $n$  you can reference elements with indices 0 through  $n - 1$ . What happens if you reference element  $-1$ ?  $n$ ?  $2n$ ?
- Well, the compiler won't complain. At runtime, the computer will happily compute a memory address based on the starting point of the array and the index. If the index is "in range", all is well. If it's not (i.e., it's "out of bounds") . . .

Slide 10

### Arrays in C, Continued

Slide 11

- (What happens if you try to access an array with an index that's out of bounds?)
- “Results are unpredictable” (“undefined behavior” in C-speak). Maybe it's outside the memory your program can access, in which case you may get the infamous “Segmentation fault” error message (or with newer compilers you may get a screenful of equally cryptic messages).  
Almost worse is if it's not — then what's at the computed memory address might be some other variable in your program, which will then be accessed/changed. This is the essence of the *buffer overflows* you hear mentioned in connection with security problems.
- What to do? *Be careful.* (Probably worth noting here that more-recent languages are apt to check for such errors.)

### Minute Essay

Slide 12

- None really — sign in.