

Classes, Objects, and Encapsulation

1-13-2012

Opening Discussion

- Have you come up with any questions about the class or topics from last time?
- Minute essay responses:
 - Definitely install Eclipse and Scala plug-in on your machines.
 - Building access.
 - No web design in this course.
 - Switching projects.
 - Linux jobs.
 - Review of major topics from last semester.

Getting the Balance

- Let's write just a bit more on our bank account example.
- We have to have enough to make sure things work.
- We also want to protect from things going wrong.

Special Methods

- Whether you are writing a class, an object, or a trait (for later), there are certain methods that are interpreted in special ways.
- Scala also has a broader naming scheme than most other languages.
- Let's make a 3-D vector class we can demonstrate things on.

Symbolic Methods

- These aren't really special, it is just the allowed names.
- “Normal” names start with a letter or underscore followed by letters, numbers, and underscores.
- You can also have names that are composed of operators symbols.
- Lastly, you can have a normal name followed by an underscore and operator symbols.
- Abusing this leads to unreadable code.

Unary Operators

- The operators -, ~, and ! can be used in a unary, prefix notation.
- If you want one of these defined for your type declare a method with unary_ followed by the symbol you want.
 - `def unary_! = ...`

Property Assignment

- Methods that take no arguments in Scala don't require parentheses.
 - `obj.value`
- Could be a method, a `val`, or a `var`.
- To preserve transparency you can make assignment methods.
 - `def value_=(v:Type) { ... }`
- This allows
 - `obj.value = something`

apply and update

- If you want to be able to use an object like a function, simply define an apply method.
- To be able to do assignments to an “index” provide update.
- This is how Arrays and other collections work.
 - `arr(5) → arr.apply(5)`
 - `arr(5)=1.3 → arr.update(5,1.3)`

Overloading

- You can make multiple methods with the same name as long as they take different arguments.
- Which type is called depends on the static type of the argument.
- Be careful with overloading. It can lead to confusion.

Companion Objects

- An object declaration with the same name as a class that is in the same file is called a companion object. It has access to private elements of the class.
- It is common to construct objects using apply methods in the companion object. That is how you get this syntax:
 - `Array(1,2,3)`
 - `List(7,5,3)`

Minute Essay

- You are supposed to write code that models a car. What are some of the classes you might create. List a few along with methods and member data.