

Trees

3-19-2012

Opening Discussion

- World of abundance.
- Discuss format change.

What is a Tree?

- You are all familiar with what normal trees look like. In CS we use the term somewhat differently, and more formally.
- To describe trees we need some basic terminology
 - Node - an element of a tree. One node is designated as the “root”
 - Edge - a directed connection from one node to another.

Tree Criteria

- Every node, C , has exactly one incoming edge from another node, P . P is said to be the parent of child node C . Root has 0.
- There is a unique path from the root to any node. The number of edges on that path is called the path length. It is also called the depth of the node.
- A node with no children is called a leaf. The path length from a node to the deepest leaf in the height of that node.

More Terms

- Following the parent-child analogy, children of the same node are called siblings. We also call any node on a path below a given node a descendant and any above an ancestor.
- You might also hear the size of a node referred to as the number of descendants of a node, including itself.
- We can also define a tree as either empty, or a root with zero or more subtrees where the root connects to the roots of those subtrees.

General Tree Implementation

- In a general tree, each node can have zero or more children. That is a lot of flexibility. We want a class to represent nodes. To get this flexibility we can use a linked list. Each node has pointers to a first child and the next sibling.
- It might be just as easy to have the child member be an Buffer that we put Nodes in. File systems are a good example of this.

Traversals

- As with any data structure one of the things you want to be able to do is to traverse through all the elements.
- Think for a while about how you would do this? There is even a question about the order you traverse them in. Do you want to process a node before you process its children or after? If before we call it a preorder traversal. If after it is a postorder traversal.

Traversals and Recursion

- The simplest way to do a traversal is through recursion. If you want to do it with a loop you have to implement a data structure to store some nodes or have the tree specially set up.
- The traverse function takes a node and calls itself once with each child node. It also does whatever the visit operation is.
- Preorder does a visit before going to children and postorder visits after going to children.
- Breadth first uses a queue, not recursion.

Coding

- For our first example of a tree, I want to make our formula parser parse to a tree.
- If we introduce variables we might evaluate the same formula many times with different values. It is inefficient to do the same string processing over and over.
- It is more efficient to parse the string once and build a tree that represents the formula then do the evaluation on that tree.
- Let's code this.

Minute Essay

- Questions?